


# crooc 0302

Device Specifications			
Safety zone	128,50 m <sup>2</sup>		
Length	14,50 m		
Width	10,86 m		
Total height	3,70 m		
Free fall height	2,10 m		
Age range	5-14 yrs		
In accordance w/ EN standards	1176-1:2009		
Availability of spare parts	Yes		
Weight of the heaviest part [kg]	269		
Dimension of the biggest part [cm]	470x275x260		



### Minimal space





#### MATERIAL SPECIFICATION

Crook series – modernly designed multifunctional playground devices made from highest quality materials. A multitude of athletic elements and long tube slides made out of stainless steel will bring lots of joy to their users.

- 80x80 mm stainless steel construction;
- Roofs and shields made out of atmospheric condition resistant HDPE or HPL polythene plates;
- Platforms and climbing walls made out of HDPE or HPL polythene plates or durable waterproof anti-skidding
- All screws covered with colorful plastic caps;
- No sharp edges or chinks that would pose a danger for jamming of the head, fingers or any other body parts;
- Steel ropes enclosed with polypropylene, linked by durable plastic elements; Tube slide made out of stainless steel;
- Tubular slide made out of stainless steel;
- Other metal elements made out of stainless steel;
- Safe rubber plug buttons topping the construction;

## ADDITIONAL COMMENTS

- The device is certified by an accrediting organization; ordeclaration of conformity;
- Embedded 80 cm deep in flat ground;
- The device is designed for public playground;
- The slide should not be positioned in a southbound direction;



Due to the free fall height of the device 0302, the EN 1176-1:2009 standard allows the following surfaces to cushion a fall. The level of granular materials requires filling in, conservation of synthetic materials is required in accordance with the manufacturer's instructions. Dimensions of the foundation are described

III IIIstaliation IIIstruction.				
Material	Description[mm]	Minimal layer	*Dimensions	
	1 1 1	thickness [mm]	foundation	
Tree bark	Grain size from 20 to 80	400	Α	
Chip	Grain size from 5 do 30	400	Α	
Sand	Grain size from 0,2 do 2	400	Α	
Gravel	Grain size from 2 do 8	400	Α	
Synthetic materials	Free fall approval ≥ 2100		A	